

AISIN CFEx+ Compatible Application Specification List

※ AISIN recommends this product for vehicles that meet the following specifications:

JAPANESE CAR APPLICATION

Daihatsu	AMMIX CVT
	AMMIX CVT Fluid DC
	AMMIX CVTF DFE
	AMMIX CVT Fluid DFC
	TC
Honda	HMMF (without starting clutch)
	HCF2
	Z-1 (CVT model, without starting clutch)
	CVT (not recommended for any Honda with starting clutch)
JASO	M315-2013 1A (> 6.5 cSt)
	M315-2013 2A (> 6.5 cSt)
Mazda	JWS 3320
Mitsubishi	CVTF-J1 (MMC Diaqueen CVT Fluid J1)
	CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid J4, J4+)
	CVTF ECO J4
	(Diaqueen) SP-III (CVT Model Only)
Nissan	NS-1, NS-2, NS-2V, NS-3, N-CVT
Subaru	iCVT
	iCVT FG
	ECVT
	Lineartronics chain CVT and CVT II Fluid, K0425Y0710 & K0425Y0711
	Lineartronics chain CVT 3 Fluid
	Lineartronics High Torque (HT) CVT Fluid, CV-30, K0421Y0700
High Torque CVTF-LV	
Suzuki	CVTF TC
	CVTF 3320
	CVTF 4401
	NS-2
	CVT Green 1 & 2/ Green 1V
Toyota	CVTF TC
	CVTF FE

CONTINENTAL CAR APPLICATION

VW/Audi	TL 521 16(G 052 516)
	TL 521 80(G 052 180)
	Multitronic
BMW Mini Cooper	EZL 799 / 83 22 0 136 376/ 83 22 0 429 154
Mini Cooper	EZL 799 / EZL 799A/ ZF CVT V1
Audi	Audi Multitronic
Fiat	Tutela CVT NG
GM	VT40 / HP CVT
GM/Saturn	DEX-CVT, GM 1940713 and 1940714
	CVTF I-Green2
Lexus	TC, FE
Dodge/Chrysler/Jeep/Mopar	NS-2, CVT+4
Opel/ Vauxhall	7-speed CVT, 95529854
Renault	Elf Matic CVT, CVT CK /SK /FK
MG Rover	EM-CVT
Volvo	CVT 4959

KOREAN CAR APPLICATION

Hyundai/Kia	CVT-1, SP-III(CVT model)
--------------------	--------------------------

OTHER CAR APPLICATION

Chery	CVT
Idemitsu	CVTF-EX1
Shell	Green 1V
Other	Punch CVTF-EX1, Fujijyuuko i-CVTF FG
Zotye	CVTs

e-Mobility Applications

Ford Escape Hybrid with eCVT
Honda e:HEV
Honda iMMD
Jatco CVT 8 Hybrid
Mazda SKYACTIVE-HYBRID
Nissan Altima Hybrid
Toyota THSII/Toyota Prius
Toyota THS 5th Gen. / Toyota Noah, Voxy etc.

※ NOT FOR USE IN AT AND DCT TRANSMISSION APPLICATIONS
2Q24 © AISIN ASIA Pte. Ltd., All Rights Reserved.